

# BAKER











# **SIDE VIEW**



# BAKER: CHILLED

A fully integrated self-serve cabinet that makes an impact in any location and allows displayed food to simply look great.

4°C operating temperature Climate Class 3M1 (25C/60%RH)

# **STANDARD FEATURES**

- GlassMax minimalist canopy (more glass/less frame) that maximises the visibility of displayed food from all angles
- Full glass top for top down viewing of displayed food
- Mitrex frame that is flush welded with mitred joins to give both robustness and a designer finish
- Integra tray race fully integrated with base: includes removable bag holder and tong holder
- > Four food display levels: three shelves plus bottom trays
- Chrome wire shelving system that is height adjustable in 25mm increments and interchangeable between horizontal and tilted positions
- CrumbCatch feature in bottom trays that collects falling crumbs and food
- > High quality European and Japanese refrigeration components
- > Fan forced air flow for even temperature distribution
- > **ClearView** front and top glass for condensation control
- Refrigeration optimised to provide a high humidity environment that maintains food quality for longer
- DuraCoat system providing a protective coating over the refrigeration coil to prevent food acid corrosion.
- SureVap self-evaporating system for condensate—no drain required
- > Condenser air vented through base—no unsightly vents
- > SlimLED under-shelf LED strip lighting with 12V safety
- Front and Rear sliding double-glazed doors on friction-free, low wear tracks (doors removable for cleaning)
- Mounted on swivel and lockable castors allowing easy movement of cabinet

### For Factory Options refer to page 60

For Cabinet Accessories refer to page 66

Model	BC6	BC9	BC12	BC15	BC18	BC24
Length	600mm	900mm	1200mm	1530mm	1770mm	2370mm
Canopy Depth*	640mm	640mm	640mm	640mm	640mm	640mm
Height	1630mm	1630mm	1630mm	1630mm	1630mm	1630mm
Available Display Area	0.92m <sup>2</sup>	1.46m²	2m²	2.6m²	2.94m²	4.03m <sup>2</sup>
Power Connection	10A Plug	10A Plug	10A Plug	10A Plug	10A Plug	10A Plug
*Add extra 15mm for protruding control panel and switches						







### **STANDARD FEATURES**

- > Open front cabinet for "grab and go"
- Stainless steel top
- Integra tray race fully integrated with base: includes removable bag holder and tong holder
- Chrome wire shelving system that is height adjustable in 25mm increments and interchangeable between horizontal and tilted positions
- High quality European heating and control components
- Designed to operate at 3 5°C in room environments up to 22°C with no air movement across open face
- DuraCoat system providing a protective coating over the refridgeration coil to prevent food acid corrosion
- SureVap self-evaporating system for condensate no drain required
- > Condensor air vented through base
- > **SlimLED** under-shelf LED strip lighting with 12V safety
- Mounted on swivel and lockable castors allowing easy movement of cabinet

For Factory Options refer to page 60 For Cabinet Accessories refer to page 66



**SIDE VIEW** 

# BAKER: CHILLED IMPULSE

A stylish open fronted cabinet that simply invites the customer in.

4°C operating temperature

Model	BCO9	BCO12	BCO15		
Length	900mm	1200mm	1530mm		
Depth*	640mm	640mm	640mm		
Height	1400mm	1400mm	1400mm		
Available Display Area	1.26 <sup>2</sup>	1.74m²	2.26m²		
Power Connection	10A Plug	10A Plug	15A Plug		
*Add extra 15mm for protruding control panel and switches					





## **STANDARD FEATURES**

- GlassMax minimalist canopy (more glass/less frame) that maximises the visibility of displayed food from all angles
- > Full glass top for top down viewing of displayed food
- > **Mitrex** frame that is flush welded with mitred joins to give both robustness and a designer finish
- Integra tray race fully integrated with base: includes removable bag holder and tong holder
- Six shelf levels; offering more extensive display area than comparable cabinets
- Chrome wire shelving system that is height adjustable in 25mm increments and interchangeable between horizontal and tilted positions
- High quality European heating and control components
- Thermostatically controlled to operate at a temperature between 30 – 95°C
- > Fan forced air flow for even heat distribution
- Rapid response element for better temperature control
- > **SlimLED** under-shelf LED strip lighting with 12V safety
- Front and Rear sliding doors on friction-free, low wear tracks (doors removable for cleaning)
- Mounted on swivel and lockable castors allowing easy movement of cabinet

# For Factory Options refer to page 60 For Cabinet Accessories refer to page 66

# BAKER: HEATED

Offering extensive space to display a wide range of product this self-serve cabinet makes heated food stand out.

Up to 95°C operating temperature

Model	BH6	BH9	BH12	BH15		
Length	600mm	900mm	1200mm	1530mm		
Canopy Depth*	640mm	640mm	640mm	640mm		
Height	1630mm	1630mm	1630mm	1630mm		
Available Display Area	1.3 <sup>2</sup>	2.1m²	2.9m²	3.8m²		
Power Connection	10A Plug	10A Plug	20A Plug	20A Plug		
*Add extra 15mm for protruding control panel and switches						

# **SIDE VIEW**





八

640

300

Front

250



### **STANDARD FEATURES**

#### GlassMax minimalist canopy (more alass/less frame) that maximises the visibility of displayed food from all angles

- > Full glass top for top down viewing of displayed food
- > Mitrex frame that is flush welded with mitred joins to give both robustness and a designer finish
- > Integra tray race fully integrated with base: includes removable bag holder and tong holder
- > Internal chrome wire shelf for holding plates
- DoubleJacket long life halogen heat lamps mounted under shelf 200
- > Gastronorm pans not supplied with unit
- > Thermostatically controlled to operate at a temperature up to 95°C
- > Drain with faucet built in
- > Can be operated wet or dry
- > Front sliding single-glazed doors on friction-free, low wear tracks (doors removable for cleaning)
- > Open at rear (no doors)
- > Mounted on swivel and lockable castors allowing easy ¥ movement of cabinet

# For Factory Options refer to page 60 For Cabinet Accessories refer to page 66

# **BAKER: BAIN MARIE**

A practical and smart looking Bain Marie cabinet for getting the most out of hot food offerings.

Up to 95°C operating temperature

Model	BB7	BB11	BB14	BB17	BB20	
Length	745mm	1070mm	1395mm	1720mm	2045mm	
Canopy Depth*	640mm	640mm	640mm	640mm	640mm	
Height	1630mm	1630mm	1630mm	1630mm	1630mm	
No. of Gastro 1/1 Pans**	2	3	4	5	6	
Power Connection	10A Plug	15A Plug	15A Plug	20A Plug	Fixed Wiring	
*Add extra 30mm for protruding control panel, switches and cable **Up to 100mm deep. (gastronorm pans not supplied)						

### **SIDE VIEW**

730

\*

\*

700

30

-**b**||4





### **STANDARD FEATURES**

- GlassMax minimalist canopy (more glass/less frame) that maximises the visibility of displayed food from all angles
- > Full glass top for top down viewing of displayed food
- > **Mitrex** frame that is flush welded with mitred joins to give both robustness and a designer finish
- Integra tray race fully integrated with base: includes removable bag holder and tong holder
- Five food display levels: four shelves plus base; offering more extensive display area than comparable cabinets
- Chrome wire shelving system that is height adjustable in 25mm increments and interchangeable between horizontal and tilted positions
- > SlimLED under-shelf LED strip lighting with 12V safety
- > Top venting to allow heat dissipation
- Front and Rear sliding doors on friction-free, low wear tracks (doors removable for cleaning)
- Mounted on swivel and lockable castors allowing easy movement of cabinet

For Factory Options refer to page 60 For Cabinet Accessories refer to page 66

# **SIDE VIEW**



# BAKER: AMBIENT

This large self-serve cabinet provides ample space to display ambient product while showing food at its best.

Model	BA6	BA9	BA12	BA15	BA18	BA24	
Length	600mm	900mm	1200mm	1530mm	1770mm	2370mm	
Canopy Depth*	640mm	640mm	640mm	640mm	640mm	640mm	
Height	1630mm	1630mm	1630mm	1630mm	1630mm	1630mm	
Available Display Area	1.13m <sup>2</sup>	1.8m²	2.5m²	3.2m <sup>2</sup>	3.6m²	5m²	
Power Connection	10A Plug	10A Plug	10A Plug	10A Plug	10A Plug	10A Plug	
*Add extra 15mm for protruding control panel and switches							